

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 1 - IDENTIFICATION

#### 1.1 Product Identifier

Product Name : Underhood Matte Black  
 Supplier Product Numbers : 12032Z

#### 1.2 Other Means of Identification

Other Identifiers : Not Available

#### 1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Rust preventative  
 Restrictions on Use : None Identified

#### 1.4 Supplier Details

Supplier Details	
Company Name	The Easthill Group, Inc./The Eastwood Company
Address	263 Shoemaker Road, Pottstown, PA 19464 - United States
Phone Number	800-343-9353
Fax Number	
Email	www.eastwood.com
Website	

#### 1.5 24 hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

### SECTION 2 - HAZARDS IDENTIFICATION

#### 2.1 Classification of the Substance or Mixture

Flam. Aerosol 1	H222	Physical Hazards	Flammable aerosol Category 1
Press. Gas (Comp.)	H280	Physical Hazards	Gases under pressure Compressed gas
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Skin Sens. 1	H317	Health Hazards	Skin sensitization, Category 1
Carc. 2	H351	Health Hazards	Carcinogenicity Category 2
Repr. 2	H361	Health Hazards	Reproductive toxicity Category 2
Stot Re 1	H372	Health Hazards	Specific target organ toxicity (repeated exposure) Category 1
Aquatic Acute 3	H402	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	H412	Environmental Hazards	Hazardous to the aquatic environment - Chronic Hazard Category 3

#### 2.2 Label Elements

##### Hazard Pictograms



##### Signal Word

**Danger**

##### Hazard Statements

H222 : Extremely flammable aerosol  
 H280 : Contains gas under pressure; may explode if heated  
 H315 : Causes skin irritation  
 H317 : May cause an allergic skin reaction

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 2/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H319 : Causes serious eye irritation  
H351 : Suspected of causing cancer  
H361 : Suspected of damaging fertility or the unborn child  
H372 : Causes damage to organs through prolonged or repeated exposure  
H402 : Harmful to aquatic life  
H412 : Harmful to aquatic life with long lasting effects

### Precautionary Statements

P202 : Do not handle until all safety precautions have been read and understood.  
P210 : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 : Do not spray on an open flame or other ignition source.  
P251 : Pressurized container: Do not pierce or burn, even after use.  
P260 : Do not breathe spray.  
P264 : Wash hands thoroughly after handling.  
P270 : Do not eat, drink or smoke when using this product.  
P272 : Contaminated work clothing must not be allowed out of the workplace  
P273 : Avoid release to the environment.  
P280 : Wear protective gloves and eye protection.  
P302+P352 : If on skin: Wash with plenty of water  
P305+P351+P338 : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 : If exposed or concerned: Get medical advice/attention.  
P314 : Get medical advice/attention if you feel unwell.  
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 : If eye irritation persists: Get medical advice/attention.  
P362+P364 : Take off contaminated clothing and wash it before reuse.  
P403 : Store in a well-ventilated place.  
P410+P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 : Dispose of contents/container to local regulations

### 2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

### 2.4 Unknown acute toxicity

39.54% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
40.76% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
15.76% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substance / Mixture

Substance / Mixture : Mixture

### 3.2 Composition

Substance name	CAS Number	% wt*	Classification
Propane	74-98-6	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
T-Butyl Acetate	540-88-5	10 - 30	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332
Acetone	67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Mineral Spirits	64742-88-7	5 - 10	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 3/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substance name	CAS Number	% wt*	Classification
4-Chlorobenzotrifluoride	98-56-6	5 - 10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Xylene	1330-20-7	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Carbon Black	1333-86-4	0.1 - 1	Carc. 2, H351
Ethyl Benzene	100-41-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
Zirconium 2-Ethylhexanoate	22464-99-9	0.1 - 1	Repr. 2, H361

Full text of hazard classes and H-statements : see section 16

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 - FIRST-AID MEASURES

### 4.1 Description of First-Aid Measures

General Measures	: If exposed or concerned: Get medical advice/attention.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
Skin Contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Lassitude (Weakness), Dermatitis, Central Nervous System Depression, Confusion, Respiratory Irritation, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Cough, Chemical Pneumonitis (Aspiration Liquid), Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Blood, Central Nervous System, Eyes, Liver, Reproductive System, Respiratory System, Skin, Kidneys.

### 4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 4/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5 - FIRE-FIGHTING MEASURES

#### 5.1 Suitable Extinguishing Media

- Extinguishing Media : Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
- Unsuitable Media : Water jet.

#### 5.2 Specific Hazards Arising from the Chemical or Mixture

- Hazardous Combustion Products : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
- Specific Hazards During Firefighting : Extremely flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

#### 5.3 Special Protective Actions for Fire-Fighters

- Firefighting Instructions : Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
- Protection during Firefighting : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- For Non-Emergency Personnel : Do not touch or walk through spill. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. No action should be taken involving any personnel without suitable training. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
- For Emergency Personnel : Observe precautions provided for non-emergency personnel above. Use personal protection as recommended in Section 8.

#### 6.2 Environmental Precautions

- Environmental Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

#### 6.3 Methods and Materials for Containment and Cleaning up

- Containment Procedures : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
- Cleanup Procedures : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

### SECTION 7 - HANDLING AND STORAGE

#### 7.1 Precautions for Safe Handling

- General Handling Precautions : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 5/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2 Conditions for Safe Storage Including Any Incompatibilities

<b>Storage Requirements</b>	: Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
<b>Incompatibilities</b>	: Segregate storage away from materials indicated in Section 10.
<b>NFPA 30B Classification</b>	: This product is classified as a Level 2 Aerosol per NFPA 30B

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control Parameters

Propane (74-98-6)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	1000 ppm
Acetone (67-64-1)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	250 ppm
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l
Methyl Ethyl Ketoxime (96-29-7)		
AIHA	WEEL TWA (ppm)	10 ppm
Carbon Black (1333-86-4)		
ACGIH	ACGIH TWA (ppm)	3 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
NIOSH	US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
California	California PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
T-Butyl Acetate (540-88-5)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	200 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	US IDLH (ppm)	1500 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	200 ppm
Xylene (1330-20-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	100 ppm
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
NIOSH	US IDLH (ppm)	900 ppm
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 6/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Xylene (1330-20-7)

California	California PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	100 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm
California	California PEL (Ceiling) (ppm)	300 ppm
Biological Exposure Index	Methylhippuric Acid in Urine (Post Shift), End of shift	1.5 g/g creatinine

### Ethyl Benzene (100-41-4)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	20 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
NIOSH	US IDLH (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	22 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	5 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	130 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	30 ppm
Biological Exposure Index	Sum of Mandelic Acid and Phenyl Glyoxylic Acid in Urine, End of shift at end of workweek	0.7 g/g creatinine

## 8.2 Exposure Controls

### Engineering Measures

: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

### Personal Protective Equipment

#### Eye / Face Protection

: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

#### Hand Protection

: Chemical-resistant gloves, tested according to ASTM F903 - 17.

#### Remarks

: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.

#### Skin and Body Protection

: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

#### Respiratory Protection

: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.

#### Compliance

: If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

#### Other Protective Equipment

: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

### Environmental Exposure Controls

: Avoid release to the environment.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Physical Properties

Boiling Point	> 55.60 °C	Melting / Freezing Point	> -96.00 °C
Flash Point, Liquid	> -17.20 °C	Flash Point, Propellant	-104.40 °C
Explosive Limits	LEL: 0.60 UEL: 13.10 vol %	Autoignition Temperature, Liquid	205.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.764 g/cm <sup>3</sup>
Molecular Weight	Not Available	Weight	6.376 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	12785.85 BTU/lb
Appearance / Color	Black	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 7/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2 Environmental Properties

Percent Volatile	82.44 % wt	VOC Regulatory	544.00 g/L (4.54 lbs/gal)
Percent VOC	42.74 % wt	VOC Actual	326.56 g/L (2.73 lbs/gal)
Percent HAP	4.07 % wt	HAP Content	31.09 g/L (0.26 lbs/gal)
Global Warming Potential	0.91 GWP	Maximum Incremental Reactivity	0.8090 g O3/g
Ozone Depletion Potential	0.00 ODP		

## SECTION 10 - STABILITY AND REACTIVITY

### 10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

### 10.2 Chemical Stability

Chemical Stability : This product is stable.

### 10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

### 10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

### 10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Halogen Compounds, Bases, Hydrogen Peroxide, Magnesium, Chlorosulfuric Acid, Potassium Chlorate.

### 10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### 11.1 Information on Toxicological Effects

#### Propane (CAS: 74-98-6 / EC: 200-827-9)

LC50 Inhalation (Rat) 658 mg/l/4h (Lit.)

#### Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat) 5800 mg/kg (Sigma-Aldrich)  
LD50 Dermal (Rabbit) 20000 mg/kg (IUCLID)  
LC50 Inhalation (Rat) 76 mg/l/4h (GESTIS Substance Database)

#### Zirconium 2-Ethylhexanoate (CAS: 22464-99-9 / EC: 245-018-1)

LD50 Oral (Rat) > 5000 mg/kg (RTECS)  
LD50 Dermal (Rabbit) > 5000 mg/kg (RTECS)  
LC50 Inhalation (Rat) > 8800 mg/m<sup>3</sup> (RTECS)

#### Methyl Ethyl Ketoxime (CAS: 96-29-7 / EC: 202-496-6)

LD50 Oral (Rat) > 930 mg/kg (RTECS)  
LD50 Dermal (Rat) > 2000 mg/kg (RTECS)  
LD50 Dermal (Rabbit) > 1000 mg/kg body weight (RTECS)  
LC50 Inhalation (Rat) 20 mg/l/4h (Lit.)

#### Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

LD50 Oral (Rat) > 15400 mg/kg (RTECS)  
LD50 Dermal (Rabbit) > 3000 mg/kg (RTECS)  
LC50 Inhalation (Rat) 27 mg/l/4h (ChemInfo)

#### T-Butyl Acetate (CAS: 540-88-5 / EC: 208-760-7)

LD50 Oral (Rat) 4500 mg/kg (RTECS)

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 8/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### T-Butyl Acetate (CAS: 540-88-5 / EC: 208-760-7)

LD50 Dermal (Rabbit)	> 2000 mg/kg (RTECS)
LC50 Inhalation (Rat)	13.3 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	5160 ppm/4h (ChemInfo)

### 4-Chlorobenzotrifluoride (CAS: 98-56-6 / EC: 202-681-1)

LD50 Oral (Rat)	13000 mg/kg (Hazardous Substances Data Bank)
LD50 Dermal (Rabbit)	3300 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	33 mg/l/4h (Hazardous Substances Data Bank)

### Xylene (CAS: 1330-20-7 / EC: 215-535-7)

LD50 Oral (Rat)	4300 mg/kg (RTECS)
LD50 Dermal (Rabbit)	12126 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	21.7 mg/l/4h (GESTIS Substance Database)
LC50 Inhalation (Rat)	6700 ppm/4h (ChemInfo)

### Ethyl Benzene (CAS: 100-41-4 / EC: 202-849-4)

LD50 Oral (Rat)	4720 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	15380 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	17.2 mg/l/4h (IUCCLID)
LC50 Inhalation (Rat)	4000 ppm/4h (ChemInfo)

### Mineral Spirits (CAS: 64742-88-7 / EC: 265-191-7)

LD50 Oral (Rat)	> 5000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	> 3000 mg/kg (Lit.)
LC50 Inhalation (Rat)	5500 ppm/4h (Lit.)

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: See Section 4.2
Skin Corrosion/Irritation	: Causes skin irritation.
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: May cause an allergic skin reaction.
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
STOT-Single Exposure	: Not classified
STOT-Repeated Exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard	: Not classified
Vaporizer	: Aerosol
Carcinogen Data	: The following ingredients are listed as known or suspected carcinogens:

### Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

IARC group	2B - Possibly Carcinogenic to Humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

### Ethyl Benzene (CAS: 100-41-4 / EC: 202-849-4)

IARC group	2B - Possibly Carcinogenic to Humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

## SECTION 12 - ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity and Ecological Properties

#### Propane (74-98-6)

Persistence and Degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF Fish	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 9/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	1.92 g O <sub>2</sub> /g substance
Theoretical Oxygen Demand	2.2 g O <sub>2</sub> /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

### Methyl Ethyl Ketoxime (96-29-7)

BCF Fish	0.5-5.8,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Fresh water; Experimental value
Log Pow	0.63 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).

### Carbon Black (1333-86-4)

LC50 Fish	> 1000 mg/l Zebra Fish - 96hr
EC50 Daphnia	> 5600 mg/l Water Flea - 24hr
EC50 Other Aquatic Organisms	> 10000 mg/l Green Algae - 72hr
Theoretical Oxygen Demand	Not applicable
Log Pow	1.09
Bioaccumulative Potential	Not bioaccumulative.

### t-Butyl Acetate (540-88-5)

LC50 Fish	240 mg/kg Rainbow Trout - 96hr
EC50 Daphnia	350 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 50% / 28 days.
BCF Fish	6.6 (BCF)
Log Pow	1.76
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).

### 4-Chlorobenzotrifluoride (98-56-6)

LC50 Fish	5.6 mg/l Bluegill Sunfish - 96h
LC50 Fish	13.5 mg/l Rainbow Trout - 24hr
EC50 Daphnia	3.68 mg/l (EC50; 48 h)
Persistence and Degradability	Biodegradability in water: no data available.
Log Pow	3.6
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

### Xylene (1330-20-7)

LC50 Fish	26.7 mg/l Fathead Minnow - 96h
EC50 Daphnia	75.49 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	72 mg/l Green Algae - 14d
Persistence and Degradability	Readily biodegradable in water.
Biochemical Oxygen Demand	1.40 - 2.53 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	2.56 - 2.91 g O <sub>2</sub> /g substance
Theoretical Oxygen Demand	3.1 g O <sub>2</sub> /g substance
BCF Fish	14.1 - 24 (BCF)
Log Pow	3.217
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	3.156

### Ethyl Benzene (100-41-4)

LC50 Fish	4.2 mg/l Rainbow Trout - 96hr
EC50 Daphnia	2.4 mg/l Water Flea - 48hr
EC50 Other Aquatic Organisms	9.68 mg/l Bacteria - 30min
EC50 Other Aquatic Organisms	4.6 mg/l Green Algae - 72hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical Oxygen Demand	1.44 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	2.1 g O <sub>2</sub> /g substance

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 10/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Ethyl Benzene (100-41-4)

Theoretical Oxygen Demand	3.17 g O <sub>2</sub> /g substance
Biodegradation	81 % 28 Days
BCF Fish	1.18
Log Pow	3.15
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.4

### Mineral Spirits (64742-88-7)





LC50 Fish	500 mg/l 96hr
EC50 Daphnia	> 100 mg/l 48hr
Chemical Oxygen Demand	0.47 mg/g
Log Pow	3.3
Bioaccumulative Potential	No bioaccumulation data available.

## SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1 Waste Treatment Methods

Waste Disposal	: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
Landfill Precautions	: Not Available.
Incineration Precautions	: ** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **.

## SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1950	UN1950	UN1950
14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 2.1	2.1	2.1
Labels	: None	2.1 - Flammable gas 	None
Limited Quantity	: 	: 	: 
EmS Code	: Not Applicable	Not Applicable	F-D, S-U
14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	: None	None	None
14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant	: No	No	No

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 11/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.6 Special Precautions

Precautions : None Identified

### 14.7 Transport in Bulk

Remarks : Not applicable for product as supplied

## SECTION 15 - REGULATORY INFORMATION

### 15.1 Federal Regulations

**SARA Section 313** : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,2,4-Trimethyl Benzene	CAS-No. 95-63-6	< 1%
Xylene	CAS-No. 1330-20-7	1 - 5%
Ethyl Benzene	CAS-No. 100-41-4	< 1%
Toluene	CAS-No. 108-88-3	< 1%
Cumene	CAS-No. 98-82-8	< 1%

**TSCA Section 12(b)** : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

**CERCLA Reportable Quantity** : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
t-Butyl Acetate	CAS-No. 540-88-5	5000 lb
Xylene	CAS-No. 1330-20-7	100 lb
Ethyl Benzene	CAS-No. 100-41-4	1000 lb
Toluene	CAS-No. 108-88-3	1000 lb
Cumene	CAS-No. 98-82-8	5000 lb

**SARA Section 311/312 Hazard Classes** : Fire hazard, Sudden release of pressure hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard.

**TSCA Inventory (United States)** : All chemical substances in this product are either listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

### 15.2 State Regulations

**California Proposition 65** : This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Quartz (14808-60-7)	Cancer	Yes	0.0153 %
Carbon Black (1333-86-4)	Cancer	Yes	0.8915 %
Ethyl Benzene (100-41-4)	Cancer	Yes	0.4478 %
Cumene (98-82-8)	Cancer	Yes	0.0171 %
Toluene (108-88-3)	Developmental Toxicity	Yes	0.0973 %
Ethyl Benzene (100-41-4)	No significance risk level (NSRL)	54 µg/day	
Toluene (108-88-3)	No significance risk level (NSRL)	7000 µg/day	

**State Right-to-Know Lists** : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Propane (74-98-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Precipitated Silica (112926-00-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Nonane (111-84-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
2-Ethylhexanoic Acid (149-57-5)	U.S. - New Jersey - Right to Know Hazardous Substance List

# SAFETY DATA SHEET

Part No. 12032Z (Aerosol)

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 12/13

## Underhood Matte Black

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,2,4-Trimethyl Benzene (95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Dipropylene Glycol Monomethyl Ether (34590-94-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Carbon Black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List
t-Butyl Acetate (540-88-5)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Xylene (1330-20-7)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Ethyl Benzene (100-41-4)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Toluene (108-88-3)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16 - OTHER INFORMATION

### Indication of changes

Section	Changed item	Change
1	Supersedes	Added
1	Revision date	Modified
1	Date of issue	Modified
1	SDS US Regulation reference	Added
2.1	GHS-US classification	Modified
2.2	Precautionary statements (GHS-US)	Modified
2.2	Hazard statements (GHS-US)	Modified
3	Composition/Information on ingredients	Modified
4	Symptoms/effects after skin contact	Modified
4	Symptoms/effects	Removed
6	Emergency procedures	Modified
7.1	Precautions for safe handling	Modified
7.2	Storage conditions	Modified
8.2	Compliance	Added
8.2	Remarks	Added
8.2	Hand Protection	Added
8.2	Environmental Exposure Controls	Added
8.2	Respiratory Protection	Added
9	Relative vapor density at 20 °C	Added
9	Appearance	Added
9	Melting point	Modified
9	Explosive limits (vol %)	Modified
9	Auto-ignition temperature	Modified
9	Specific gravity / density	Modified
12.1	Ecology - general	Modified
14	User Precautions	Added
14	EmS Code (Column 15 in IMDG Book 2)	Added
15	Select the Appropriate Proposition 65 Notice	Modified

### Full Text of H-Statements

H Code	H Phrase
H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

# SAFETY DATA SHEET

**Part No. 12032Z (Aerosol)**

Print Date: 3/2/2018  
Revision Date: 3/2/2018  
Supersedes Date: 6/26/2017  
Issue Date: 9/28/2011  
Version: 4.0 (EN)-US  
Page: 13/13

## Underhood Matte Black

*according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations*