



Safety Data Sheet

Copyright,2014,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-2116-2	Version number:	3.02
Issue Date:	21/07/2014	Supersedes date:	23/09/2013

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Perfect-It™ Ultrafine Machine Polish, PN 06068 06069 06073 06074, 39062

Product Identification Numbers

60-4550-3493-8

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is NOT classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Not applicable.

2.2. Label elements

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Causes mild skin irritation.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	40 - 70
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30
Dodecamethylcyclohexasiloxane	540-97-6	7 - 15
Aluminium oxide	1344-28-1	3 - 8
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4	1 - 5
Mineral Oil	64741-89-5	< 2

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning: A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep from freezing. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m ³	
Aluminium oxide	1344-28-1	CMRG	TWA:1 fiber/cc	
Paraffin oil	64741-88-4	Australia OELs	TWA(as mist)(8 hours):5 mg/m ³	
Solvent-Refined Heavy Paraffinic	64741-88-4	CMRG	TWA:5 mg/m ³	

3M™ Perfect-It™ Ultrafine Machine Polish, PN 06068 06069 06073 06074, 39062

Petroleum Distillates				
Paraffin oil	64741-89-5	Australia OELs	TWA(as mist)(8 hours):5 mg/m ³	
Hydrotreated Light Petroleum Distillates	64742-47-8	CMRG	TWA:165 ppm	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile rubber.

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Blue liquid. solvent odour
Odour threshold	<i>No data available.</i>
pH	7.5 - 8.5
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	100 °C
Flash point	> 110 °C [<i>Test Method:</i> Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapour density	4.5 [<i>Ref Std:</i> AIR=1]
Density	0.911 - 1.007 g/ml
Relative density	0.911 - 1.007 [<i>Ref Std:</i> WATER=1]
Water solubility	Appreciable
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
Hazardous air pollutants	0.001 % weight [<i>Test Method:</i> Calculated]
Volatile organic compounds (VOC)	1 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0.1 % weight [<i>Test Method:</i> calculated per CARB title 2]
Percent volatile	74.2 % [<i>Test Method:</i> Estimated]
VOC less H2O & exempt solvents	1 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong acids.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be

reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause target organ effects after ingestion.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.0 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Dermal	Rabbit	LD50 > 2,000 mg/kg
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Ingestion	Rat	LD50 > 5,000
Mineral Oil	Dermal	Rabbit	LD50 > 5,000 mg/kg
Mineral Oil	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

3M™ Perfect-It™ Ultrafine Machine Polish, PN 06068 06069 06073 06074, 39062

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Rabbit	Minimal irritation
Mineral Oil	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Rabbit	Mild irritant
Mineral Oil	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not sensitizing
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Guinea pig	Not sensitizing
Mineral Oil	Guinea pig	Not sensitizing

Respiratory Sensitisation

Name	Species	Value
------	---------	-------

Germ Cell Mutagenicity

Name	Route	Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
Solvent-Refined Heavy Paraffinic Petroleum Distillates	In Vitro	Some positive data exist, but the data are not sufficient for classification
Mineral Oil	In vivo	Not mutagenic
Mineral Oil	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Mineral Oil	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to development	Rat	NOAEL 1,000	pre mating & during gestation

				mg/kg/day	
--	--	--	--	-----------	--

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	endocrine system liver respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminium oxide	Inhalation	pneumoconiosis pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.21 mg/l	28 days
Mineral Oil	Dermal	hematopoietic system liver kidney and/or bladder	All data are negative	Rabbit	NOAEL 5,000 mg/kg/day	3 weeks

Aspiration Hazard

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Aspiration hazard
Mineral Oil	Aspiration hazard

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Mineral Oil	64741-89-5	Green algae	Experimental	96 hours	EC50	>100 mg/l
Mineral Oil	64741-89-5	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Mineral Oil	64741-89-5	Green algae	Experimental	96 hours	NOEC	100 mg/l
Mineral Oil	64741-89-5	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Dodecamethyl cyclohexasiloxane	540-97-6		Data not available or insufficient for classification			
Hydrotreated Light Petroleum Distillates	64742-47-8		Data not available or insufficient for classification			
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dodecamethyl cyclohexasiloxane	540-97-6	Experimental Biodegradation	28 days	CO2 evolution	4.46 % weight	Other methods
Aluminium	1344-28-1	Data not	N/A	N/A	N/A	N/A

3M™ Perfect-It™ Ultrafine Machine Polish, PN 06068 06069 06073 06074, 39062

oxide		available or insufficient for classification				
Mineral Oil	64741-89-5	Experimental Biodegradation	28 days	CO2 evolution	22 % weight	OECD 301B - Modified sturm or CO2
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dodecamethyl cyclohexasiloxane	540-97-6	Experimental BCF - Fathead Mi	49 days	Bioaccumulation factor	1160	OECD 305E - Bioaccumulation flow-through fish test
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mineral Oil	64741-89-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

SECTION 16: Other information

Revision information:

Conversion to GHS format SDS.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Australia SDSs are available at www.3m.com.au