## **TECHNICAL DATA SHEET**



-DeRuster & DeGreaser-

Product: ANTI-OX

**DeRuster / DeGreaser** 

Product Code: ANTIOX1L, ANTIOX5L, ANTIOX20L, ANTIOX 200L

Introduction: Oxytech's ANTI-OX is a versatile phosphoric acid based deruster, degreaser and

phosphator all in one. ANTI-OX is designed to attack rust while removing oils and contaminants from the metal surface. ANTI-OX is also suitable as a bath solution for

soaking rusted parts and bolts.

Applications: Automotive fabrication & restoration, pre-paint treatment, rust removal

Pack Sizes: 1 Litre, 5 Litre, 20 Litre & 200 Litre

Application Schedule: HEAVY RUST: Apply undiluted and scrub with a wire brush or wire wheel. Rinse

thoroughly with water. Repeat if necessary.

MEDIUM & LIGHT RUST: Dilute 1:10 with water and apply with brush or saturated rag. Allow 10-15 minutes for reaction and remove excess ANTI-OX with clean water damp rags. ANTI-OX can be applied undiluted for faster treatment on raw steel only. Remove

excess ANTI-OX with a clean water damp rag.

UNRUSTED/METAL CONDITIONING: Dilute ANTI-OX 1:25 with water and apply by brush or saturated rag. Allow to dry and remove white powder with a clean water damp rag.

Once metal has been treated with ANTI-OX, a light coating of EASY PHOS can be applied

to maintain the rust free surface.

Coverage: 1 Litre of ANTI-OX will treat up to 30m<sup>2</sup> of surface. Heavier application will reduce this

considerably.

Health & Safety: Contains PHOSPHORIC ACID

Wear gloves and goggles. If on skin, wash immediately.

Care should be taken when applying ANTI-OX. Apply in a well ventilated area. Please

read MSDS for further information.

Proudly developed and manufactured in Australia

