

AfterBlast TECHNICAL DATA SHEET



DESCRIPTION

RestoFinish AfterBlast is a single stage, bare metal preserver. Designed to protect and preserve bare steel from surface rust and oils during temporary storage and handling. AfterBlast is also the perfect temporary sealer for "cut throughs" to metal during the "RestoFinish Process".



APPLICATION

AfterBlast is ready to use, no mixing or dilution required. One thin even coat is all that is required. Ensure surface is free from rust, paint, dust and previous coatings. If surface rust is present, use RestoFinish RusGo as per Technical Data Sheet (TDS). Remove sanding debris, blow down with clean dry air and clean surface with RestoFinish Metal Cleaner as per TDS to ensure surface is free from any contaminants.

SPRAY: Apply one (1) even coat with consistent overlap. NOTE: One (1) even coat is ideal.

WIPE: Using a clean disposable cloth, decant required amount into a Dangerous Goods compatible container. Dampen cloth and wipe surface with one medium coat. Add more as required.

COATING: When ready to overcoat, please refer to RestoFinish Epoxycoat TDS. Excessive use or wet coats can create discoloration. Discoloration can also occur when metal is not previously cleaned and AfterBlast reacts with contaminants on surface. Wear protective gloves and use a clean disposable cloth.



POT LIFE

Use once de-canned within one (1) hour. Dispose of unused product. Do not return to original container. Use within temperature range 15° C - 30° C.



HEALTH & SAFETY

Please refer to Safety Data Sheet (SDS). Use in well ventilated area. Do not breathe fumes or vapour. Eye and skin protection must be worn. Wash from skin immediately. If Swallowed – DO NOT INDUCE VOMITING – give a glass of water. SEEK MEDICAL ATTENTION.

HEALTH AND SAFETY FOR PROFESSIONAL USE ONLY. Full instructions must be read before use. Plese refer to RestoFinish Safety Data Sheets (SDS) and product labels for full Health and Safety details and product handling instructions. IMPORTANT: This product contains hazardous materials and appropriate PPE (personal protective equipment) must always be used.

Products are suitable for professional use only. The data on this sheet indicate typical values. As application variables are a major factor in product performance, this information should serve as a general guide only. The data included in this application are based on our present knowledge and experience. RestoFinish assumes no responsibility or liability for use of this information. UNLESS RESTOFINISH AGREES IN WRITING, RESTOFINISH ASSUMES NO WARRANTIES, EXPRESS OR IMPLIED, AND REPUDIATES ALL IMPLIED WARRANTIES INCLIDING WARRANTIES OF MERCHANTABILITY OR SUITABILITY FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. RESTOFINISH MAGES. Your only remedy for any fault in this product is the replacement of the defective product, or a refund of the product purchase price, at our discretion. The latest version supersedes all preceding versions. You can obtain the most recent version from our website www.restofinish.com.au or directly from your sales agent. It is the responsibility of the beneficiary of our products to verify that any proprietary rights and existing laws and legislation are observed. RestoFinish® (a division of Global Finish Pty Ltd). All rights reserved. v0423

IN AN EMERGENCY DIAL 000 (AUS) or 111 (NZ) POLICE OR FIRE BRIGADE

RESTOFINISH A Division of Global Finish Pty Ltd 6/8 Stockyard Place, West Gosford NSW Australia 2250 Telephone: + 61 (2) 4321 0339 Facsimile: + 61 (2) 4321 0338 Email: info@restofinish.com.au www.restofinish.com.au